

ARCUS SPEC 3D LARGE - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White

Features

The Arcus Combo System combines standard cut and free cut capabilities to provide precise, made-to-order lengths, utilizing Standard Cuts for the majority of the runs, with Free Cuts reserved only for the finishing segments. This combo usage achieves cost savings of 20 - 40% versus using Free Cuts for the entire length. Both Arcus Standard Cut and Free Cut maintain consistent binning and brightness.

The system is suitable for indoor and outdoor applications, and delivers exceptional performance with a CRI over 95, brightness of up to 275 lm/ft, and 1-step binning, ensuring robustness and design flexibility.

Applications

Living rooms, TV walls, feature walls, under-cabinet areas, staircases, ceiling coves, hallways, etc.



RoHS

ONE
BIN24V
DC

Date



Fixture type

Project name


Project phase



Combo System



Dimensions



*FT/FO end caps are flush-finished with the strip body.

Order Code

Model	Environment	Voltage	CCT	Power	End Cap	Left Feed Entry
AS3DL	D4-Dry (IP54)	24V-DC24V	27K-2700K	3.0-3.05W/ft	FT Flush translucent	F Front OW Open wire 3.28ft (1m)
AS3DLFC	W7-Wet (IP67)		30K-3000K		FO Flush opaque	B Bottom MC Male connector with 0.98ft (30cm) cable
			35K-3500K			S Side FC Female connector with 0.98ft (30cm) cable
			40K-4000K			C Closed NA Only for Closed Feed Entry

*AS3DLFC: Free Cut delivers precise field-cut lengths for the last segment while keeping in line with standard cut in dimensions, binning, output, and mounting for a uniform appearance.

*Flush translucent and opaque are factory-made only.

Assembly Builder

Assembly Builder

Right Feed Entry			Length	
F Front	OW	Open wire 3.28ft (1m)	Max nominal	16.4ft (5m)
B Bottom	MC	Male connector with 0.98ft (30cm) cable	Increment	2.46in. (62.5mm)
S Side	FC	Female connector with 0.98ft (30cm) cable	* For ARCUS SPEC 3D LARGE	
C Closed	NA	Only for Closed Feed Entry		

*We will manufacture to the requested length considering the increment length.

Mounting Order Code

Product Code

Please select on the Mounting Options page.

ARCUS SPEC 3D LARGE – COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White

Lumen Output (lm/ft)


Temp./Color	3.05W/ft
2700K	250
3000K	260
3500K	272
4000K	275
Max. Run for Class 2*	16.4ft (5m) ¹ 13.1ft (4m) ²
Max. Run Supported Length	16.4ft (5m) ¹ 13.1ft (4m) ²

1. Max run for standard cut.
2. Max run for Free cut.

Technical Details

Efficacy	90.2lm/w @4000K 3.05W
CRI	CRI > 95
Beam Angle	120°
LED MacAdam	1 steps
Average Life (L70)	> 44,000 hours
Storage Temperature	-40-140°F (-40°C - 60°C)
Operating Temperature	-40-113°F (-40°C - 45°C)

Photometry




Zonal Lumen Summary 3000K

Zone	Lumen	% Fixture
0-30	207.8	25.2%
0-40	339.9	41.2%
0-60	603.2	73.2%
0-90	798.0	96.8%
0-180	824.5	100%

UNIT: CD

- C0/180, 111.6
— C30/210, 112.6
— C60/240, 113.9
— C90/270, 114.4




ARCUS SPEC 3D LARGE – COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)


3D Bending · Static White

Feed Entry / End Cap Options


FT: Flush translucent end cap – IP54/IP67, factory-made only



FO: Flush opaque end cap – IP54/IP67, factory-made only




SEC: Silicone end cap – IP54/IP67, order separately



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28ft (1m), 18 AWG (wire length customizable)



MC: Male connector, **Wet**
Standard 0.98ft (30cm), 18 AWG





FC: Female connector, **Wet**
Standard 0.98ft (30cm), 18 AWG

ARCUS SPEC 3D LARGE - COMBO SYSTEM


(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White


Mounting Options

**ARCUS-L-SC**



Name	Straight surface channel
Material	Aluminum
Standard Length	3.28ft (1M)

**ARCUS-L-BC**


Name	Bendable surface channel
Material	Aluminum
Standard Length	3.28ft (1M)
Min. bending radius	23.6in. (600mm)

**ARCUS-L-RC**



Name	Straight recessed channel
Material	Aluminum
Standard Length	3.28ft (1M)

**ARCUS-L-MC**



Name	Mud-in channel
Material	Aluminum
Standard Length	3.28ft (1M)

**ARCUS-L-BMC**



Name	Bendable mud-in channel
Material	Aluminum
Standard Length	3.28ft (1M)
Min. bending radius	23.6in. (600mm)

**ARCUS-L-SCS**


Name	Straight surface channel with silicone groove
Material	Aluminum
Standard Length	3.28ft (1M)

**ARCUS-L-LBC**

Name	Light-block channel
Material	Aluminum
Standard Length	3.28ft (1M)

**ARCUS-L-PC**

Name	PC channel
Material	Polycarbonate
Standard Length	3.28ft (1M)


**ARCUS-L-CL**

Name	Mounting clip
Material	Aluminum
Standard Length	0.98in. (25mm)

ARCUS SPEC 3D LARGE – COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White



ARCUS-L-LS

Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	0.79in. (20mm)

* ARCUS-L-LS can be installed with aluminum channel ARCUS-L-SC.

ARCUS-L-AC

Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	1 in. (25.5mm)


* ARCUS-L-LS can be installed with aluminum channel ARCUS-L-SC.

ARCUS-L-RC-SPC

Name	Spring clip
Standard Pkg	1pcs

* ARCUS-L-RC-SPC must be installed with aluminum channel ARCUS-L-RC.

End Caps (Optional, purchase for extra)



ARCUS-L-SEC-C

Silicone closed end cap

ARCUS-L-SEC-F-2P

Silicone end cap front entry with 0.98ft (30cm) cable, 2 pin

ARCUS-L-SEC-S-2P

Silicone end cap side entry with 0.98ft (30cm) cable, 2 pin

ARCUS-L-SEC-B-2P

Silicone end cap bottom entry with 0.98ft (30cm) cable, 2 pin

Additional Accessories (Optional, purchase for extra)



MCW-2P-67

Male connector with 0.98ft (30cm) white cable, 2 pin, IP67, Wet, 18 AWG

FCW-2P-67

Female connector with 0.98ft (30cm) white cable, 2 pin, IP67, Wet, 18 AWG

MCB-2P-67

Male connector with 0.98ft (30cm) black cable, 2 pin, IP67, Wet, 18 AWG

FCB-2P-67

Female connector with 0.98ft (30cm) black cable, 2 pin, IP67, Wet, 18 AWG

ARCUS SPEC 3D LARGE – COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KV-24030-ASW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KV-24060-ASW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KV-24096-ASW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)

Phase cut/Triac-dimmable

Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVF-24030-TDW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVF-24060-TDW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVF-24096-TDW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVF-24030-TDWJ	30W				Yes	Dry/Damp	6.5 x 3.6 x 1in. (16.5 x 9.2 x 2.6cm)
KVF-24060-TDWJ	60W						7.4 x 3.6 x 1in. (18.8 x 9.2 x 2.6cm)
KVF-24096-TDWJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.3 x 4.1cm)
KVF-24192-TDWJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVF-24288-TDWJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVF-24384-TDWJ	384W (96Wx4)						12.7 x 5.5 x 1.9in. (32.3 x 14 x 4.8cm)

4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)

Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVD-24030-DIM	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVD-24060-DIM	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVD-24096-DIM	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVD-24030-DIMJ	30W				Yes	Dry/Damp	6.5 x 3.6 x 1in. (16.5 x 9.2 x 2.6cm)
KVD-24060-DIMJ	60W						7.4 x 3.6 x 1in. (18.8 x 9.2 x 2.6cm)
KVD-24096-DIMJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.3 x 4.1cm)
KVD-24192-DIMJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVD-24288-DIMJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVD-24384-DIMJ	384W (96Wx4)						12.7 x 5.5 x 1.9in. (32.3 x 14 x 4.8cm)

5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)

Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KVG-24030-DW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (15.5 x 5.4 x 2cm)
KVG-24060-DW	60W						7 x 2.4 x 0.9in. (17.8 x 6.1 x 2.4cm)
KVG-24096-DW	96W					Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (23 x 7 x 4.3cm)
KVG-24030-DWJ	30W				Yes	Dry/Damp	6.5 x 3.7 x 1.6in. (16.5 x 9.5 x 4cm)
KVG-24060-DWJ	60W						7.4 x 3.7 x 1.6in. (18.8 x 9.5 x 4cm)
KVG-24096-DWJ	96W						8.7 x 3.7 x 1.6in. (22 x 9.5 x 4cm)
KVG-C24192-DWJ	192W (96Wx2)						10.9 x 4.3 x 1.8in. (27.8 x 11 x 4.5cm)
KVG-C24288-DWJ	288W (96Wx3)						11.9 x 4.3 x 1.8in. (30.1 x 11 x 4.5cm)
KVG-C24384-DWJ	384W (96Wx4)						12.8 x 5.5 x 1.9in. (32.5 x 14 x 4.8cm)


ARCUS SPEC 3D LARGE - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)


3D Bending · Static White

Wiring Diagram

Non-dimmable




Phase cut/Triac-dimmable



4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)



5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)



24V Voltage Drop & Maximum Wire Length Chart

ARCUS SPEC 3D LARGE – COMBO SYSTEM

3D Bending · Static White

(Standard Cut + Free Cut Finishing Piece)

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG
5W / 0.2A	1730 ft (527.3 m)	784 ft (238.9 m)	397 ft (121.0 m)	263 ft (80.2 m)	175 ft (53.3 m)	131 ft (39.9 m)	107 ft (32.6 m)
10W / 0.4A	865 ft (263.6 m)	392 ft (119.4 m)	199 ft (60.7 m)	132 ft (40.2 m)	88 ft (26.8 m)	66 ft (20.1 m)	54 ft (16.5 m)
15W / 0.6A	577 ft (175.9 m)	261 ft (79.6 m)	132 ft (40.2 m)	88 ft (26.8 m)	58 ft (17.7 m)	44 ft (13.4 m)	36 ft (11.0 m)
20W / 0.8A	433 ft (132.0 m)	196 ft (59.7 m)	99 ft (30.2 m)	66 ft (20.1 m)	44 ft (13.4 m)	33 ft (10.1 m)	27 ft (8.2 m)
25W / 1.0A	346 ft (105.5 m)	157 ft (47.9 m)	79 ft (24.1 m)	53 ft (16.2 m)	35 ft (10.7 m)	26 ft (7.9 m)	22 ft (6.7 m)
30W / 1.3A	289 ft (88.1 m)	131 ft (39.9 m)	66 ft (20.1 m)	44 ft (13.4 m)	29 ft (8.8 m)	22 ft (6.7 m)	18 ft (5.5 m)
35W / 1.5A	248 ft (75.6 m)	112 ft (34.1 m)	57 ft (17.4 m)	38 ft (11.6 m)	25 ft (7.6 m)	19 ft (5.8 m)	15 ft (4.6 m)
40W / 1.7A	217 ft (66.1 m)	98 ft (29.9 m)	50 ft (15.2 m)	33 ft (10.1 m)	22 ft (6.7 m)	16 ft (4.9 m)	13 ft (4.0 m)
45W / 1.9A	192 ft (58.5 m)	87 ft (26.5 m)	44 ft (13.4 m)	29 ft (8.8 m)	19 ft (5.8 m)	14 ft (4.3 m)	12 ft (3.7 m)
50W / 2.1A	173 ft (52.7 m)	78 ft (23.8 m)	40 ft (12.2 m)	26 ft (7.9 m)	18 ft (5.5 m)	13 ft (4.0 m)	11 ft (3.4 m)
55W / 2.3A	157 ft (47.9 m)	71 ft (21.6 m)	36 ft (11.0 m)	24 ft (7.3 m)	16 ft (4.9 m)	12 ft (3.7 m)	10 ft (3.0 m)
60W / 2.5A	144 ft (43.9 m)	65 ft (19.8 m)	33 ft (10.1 m)	22 ft (6.7 m)	15 ft (4.6 m)	11 ft (3.4 m)	9 ft (2.7 m)
65W / 2.7A	133 ft (40.5 m)	60 ft (18.3 m)	30 ft (9.1 m)	20 ft (6.1 m)	14 ft (4.3 m)	10 ft (3.0 m)	8 ft (2.4 m)
70W / 2.9A	124 ft (37.8 m)	56 ft (17.1 m)	28 ft (8.5 m)	19 ft (5.8 m)	13 ft (4.0 m)	10 ft (3.0 m)	8 ft (2.4 m)
75W / 3.1A	116 ft (35.4 m)	52 ft (15.9 m)	26 ft (7.9 m)	17 ft (5.2 m)	12 ft (3.7 m)	9 ft (2.7 m)	7 ft (2.1 m)
80W / 3.3A	109 ft (33.2 m)	49 ft (14.9 m)	25 ft (7.6 m)	16 ft (4.9 m)	11 ft (3.4 m)	8 ft (2.4 m)	7 ft (2.1 m)
85W / 3.5A	103 ft (31.4 m)	46 ft (14.0 m)	23 ft (7.0 m)	15 ft (4.6 m)	10 ft (3.0 m)	8 ft (2.4 m)	6 ft (1.8 m)
90W / 3.8A	97 ft (29.6 m)	44 ft (13.4 m)	22 ft (6.7 m)	15 ft (4.6 m)	10 ft (3.0 m)	7 ft (2.1 m)	6 ft (1.8 m)
96W / 4.0A	91 ft (27.7 m)	41 ft (12.5 m)	21 ft (6.4 m)	14 ft (4.3 m)	9 ft (2.7 m)	7 ft (2.1 m)	6 ft (1.8 m)