

Beamever

FORTE 3D LARGE RGBW

Designer's Custom Playground

Outdoor · 3D Bending · RGBW


Features

- Robust & uniform silicone body with changeable RGBW colors
- Multi-directional bending design for flexible installations
- IP68 rated, ideal for outdoor uses, not for underwater project
- 3 years warranty


Applications

Architectural facades, building contours, landscape accents, bridges, walkways, transit hubs, staircases, and outdoor feature walls, etc.

Date	Fixture type
Project name	Project phase



Bending Directions & Diameters



Order Code

Model	Environment	Voltage	CCT	Power	End Cap	Left Feed Entry	
F3DL	W8-Wet (IP68)	24V-DC24V	RGBW27K-RGBW2700K RGBW30K-RGBW3000K RGBW35K-RGBW3500K RGBW40K-RGBW4000K	4.1-4.12W/ft	FT Flush Translucent FO Flush Opaque	F Front B Bottom S Side C Closed	OW Open wire 3.28ft (1m) OA Open Wire with Anti-Wicking Ferrule MC Male connector with 11.8in. (300mm) cable FC Female connector with 11.8in. (300mm)cable NA Only for Closed Feed Entry

Assembly Builder

Assembly Builder

Right Feed Entry			Length	
F Front	OW	Open wire 3.28ft (1m)	Max. nominal	26.2ft (8m)
B Bottom	OA	Open Wire with Anti-Wicking Ferrule	Increment	2.8in. (71.43mm)
S Side	MC	Male connector with 11.8in. (300mm) cable		
C Closed	FC	Female connector with 11.8in. (300mm)cable		
	NA	Only for Closed Feed Entry		

*We will list the nearest actual manufacturing length on the quotation, based on your requested length.

Mounting Order Code

Product Code
Please select on the Mounting Options page

Beamever

FORTE 3D LARGE RGBW

Designer's Custom Playground

Outdoor · 3D Bending · RGBW


Lumen Output (lm/ft)

CCT	4.12W/ft
R	9
G	33
B	6
W27K	29
W30K	30
W35K	30
W40K	30
RGBW27K	75
RGBW30K	77
RGBW35K	79
RGBW40K	79
Max. Run for Class 2*	19.4ft (5.9m)
Max. Run Supported Length	26.2ft (8m)

*Typically installations in USA and Canada comply with Class 2 requirements

Photometry

F3DL-W8-24V-RGBW30K-4.1-FT-F-OW-F-OW
FORTE 3D LARGE RGBW, 3D Bend, RGBW30K, 4.1W/ft



Zonal Lumen Summary

Zone	Lumen	% Fixture
0-30	20.1	25.9%
0-40	32.9	42.5%
0-60	58.2	75.2%
0-90	76.1	98.4%
0-180	77.4	100.0%

Technical Details

Efficacy	19lm/W @RGBW30K 4.12W
CRI	Ra≥80
Beam Angle	110°
Average Life (L70B10)	>32,000 hours
Storage Temperature	-40°F~-149°F (-40°C~ 65°C)
Operating Temperature	-40°F~-149°F (-40°C~ 65°C)

Beamever


FORTE 3D LARGE RGBW

Designer's Custom Playground


Outdoor · 3D Bending · RGBW

Feed Entry / End Cap Options


FT: Flush Translucent – IP68, factory-made only




FO: Flush Opaque – IP68, factory-made only



Silicone end cap – IP67, for field cuttable only



Mechanical end cap with screws – IP67, for field cuttable only



Connector Wire Options




OW: Open wire, **Dry only**
Standard 11.81in. (300mm), 20 AWG,
wire length customizable



MC: Male connector, **Wet**
Standard 11.81in. (300mm), 20 AWG





FC: Female connector, **Wet**
Standard 11.81in. (300mm), 20 AWG





OA: Open Wire with **Anti-Wicking Ferrule**, **Wet**
Standard 11.81in. (300mm), 20 AWG,
Protects against water ingress through the power cable

Mounting Options





NF1617-SC

Name	Straight surface channel
Material	Aluminum
Standard Length	3.28ft (1m)




NF1617-BC

Name	Bendable surface channel
Material	Aluminum
Standard Length	3.28ft (1m)
Min. Bending Radius	11.8in.(300mm)





NF1617-RC

Name	Straight recessed channel
Material	Aluminum
Standard Length	3.28ft (1m)




NF1617-MC

Name	Mud-in channel
Material	Aluminum
Standard Length	3.28ft (1m)





NF1617-BMC

Name	Bendable mud-in channel
Material	Aluminum
Standard Length	3.28ft (1m)
Min. Top Bending Radius	11.8in.(300mm)
Min. Side Bending Radius	31.50in.(800mm)




NF1617-SCS

Name	Straight surface channel
Material	Aluminum with silicone groove
Standard Length	3.28ft (1m)



NF1617-LBC

Name	Light-block channel
Material	Aluminum
Standard Length	3.28ft (1m)



NF1617-PC

Name	PC channel
Material	Polycarbonate
Standard Length	3.28ft (1m)

Mounting Options




Table with 2 columns: Property and Value. Rows include Name (NF1617-BPC), Material (Polycarbonate), Standard Length (3.28ft (1m)), and Min. Bending Radius (5.91in. (150mm)).





Table with 2 columns: Property and Value. Rows include Name (NF1617-CL), Material (Aluminum), and Standard Length (0.98in. (25mm)).




Table with 2 columns: Property and Value. Rows include Name (NF1617-LS), Material (Aluminum), and Standard Length (0.79in. (20mm)). A note states: * NF1617-LS must be installed with NF1617-SC.




Table with 2 columns: Property and Value. Rows include Name (NF1617-AC), Material (Stainless steel), and Standard Length (1 in. (25.5mm)). A note states: * NF1617-AC must be installed with NF1617-SC.





Table with 2 columns: Property and Value. Rows include Name (NF1617-RC-SPC), Standard Pkg (1pcs), and a note: * NF1617-RC-SPC must be installed with NF1617-RC.


Beamever

FORTE 3D LARGE RGBW

Designer's Custom Playground

Outdoor · 3D Bending · RGBW

Silicone End Caps (Optional, purchase for extra)



NF1617-SEC-C
Silicone closed end cap



NF1617-SEC-F-5P
Silicone end cap front entry with 11.8lin. (300mm) cable, 5 pin



NF1617-SEC-S-5P
Silicone end cap side entry with 11.8lin. (300mm) cable, 5 pin



NF1617-SEC-B-5P
Silicone end cap bottom entry with 11.8lin. (300mm) cable, 5 pin

Additional Accessories (Optional, purchase for extra)



MCW-5P-67
Male connector, 11.8lin. (300mm) white cable, 5 pin, IP67, Wet, 20 AWG



FCW-5P-67
Female connector, 11.8lin. (300mm) white cable, 5 pin, IP67, Wet, 20 AWG




MCB-5P-67
Male connector, 11.8lin. (300mm) black cable, 5 pin, IP67, Wet, 20 AWG



FCB-5P-67
Female connector, 11.8lin. (300mm) black cable, 5 pin, IP67, Wet, 20 AWG



ADJS
1 Adjustable Angle Scissors Set, with 4 Spare Blades



NF1617-IT
Installation tool for NF1617-BPC

Drivers

Non-dimmable

Code	Max Load	Input	Output	Class 2	With Junction Box	Environment	Size (L x W x H)
KV-24030-ASW	30W	100-277VAC	24V	Yes	No	Dry/Damp	6.1 x 2.1 x 0.8in. (155 x 54 x 20mm)
KV-24060-ASW	60W	100-277VAC	24V	Yes	No	Dry/Damp	7 x 2.4 x 0.9in. (178 x 61 x 24mm)
KV-24096-ASW	96W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	9.1 x 2.8 x 1.7in. (230 x 70 x 43mm)


DMX-dimmable

Code	Max Load	Input	Output	Class 2	Environment	Size (L x W x H)
KVX-24100-4C-A	100W	100-277VAC	24V	Yes	Dry/Damp/Wet	9.05 x 3.07 x 0.98 in. (230 x 78 x 25 mm)
KVX-24150-4C-A	150W	100-277VAC	24V	No	Dry/Damp/Wet	10.90 x 3.07 x 0.98 in. (277 x 78 x 25 mm)
KVX-24200-4C-A	200W	100-277VAC	24V	No	Dry/Damp/Wet	10.90 x 3.07 x 0.98 in. (277 x 78 x 25 mm)
KVX-24300-4C-A	300W	100-277VAC	24V	No	Dry/Damp/Wet	11.85 x 3.07 x 0.98 in. (301 x 78 x 25 mm)

DMX-Decoders & Controllers Options

Type	Code	Description	Size (L x W x H)
DMX-Decoders	LT-904	4 channels output, up to 576W output power	4.80 x 4.33 x 1.46 in. (122 x 110 x 37 mm)
DMX-Decoders	LT-916	16 channels output, up to 1152W output power	7.09 x 4.80 x 1.54 in. (180 x 122 x 39 mm)
DMX-Decoders	LT-932	32 channels output, up to 1728W output power	11.81 x 4.80 x 1.54 in. (300 x 122 x 39 mm)
Controllers	DINA-DR micro	DMX 60 channels stand-alone controller with 10 scenes and USB programming	2.05 x 1.14 x 0.94 in. (52 x 29 x 24 mm)
Controllers	SLESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes	3.03 x 3.43 x 1.57 in. (77 x 87 x 40 mm)
Controllers	STICK-CW4	DMX 1024 channels controller with 36 scenes and 6 touch buttons	4.17 x 5.75 x 0.39 in. (106 x 146 x 10 mm)

Wiring Diagram



24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	1588ft (484.0m)	999ft (304.5m)	628ft (191.4m)	395ft (120.4m)	248ft (75.5m)	156ft (47.5m)	98ft (29.8m)	61ft (18.5m)
20W / 0.8A	794ft (242.0m)	499ft (152.1m)	314ft (95.7m)	197ft (60.0m)	124ft (37.8m)	78ft (23.7m)	49ft (14.9m)	30ft (9.1m)
30W / 1.3A	529ft (161.2m)	333ft (101.5m)	209ft (63.7m)	131ft (39.9m)	82ft (24.9m)	52ft (15.8m)	32ft (9.7m)	20ft (6.1m)
40W / 1.7A	397ft (121.0m)	249ft (75.9m)	157ft (47.8m)	98ft (29.8m)	62ft (18.9m)	39ft (11.8m)	24ft (7.3m)	15ft (4.5m)
50W / 2.1A	317ft (96.6m)	199ft (60.6m)	125ft (38.1m)	79ft (24.0m)	49ft (14.9m)	31ft (9.4m)	19ft (5.7m)	12ft (3.6m)
60W / 2.5A	264ft (80.4m)	166ft (50.6m)	104ft (31.7m)	65ft (19.8m)	41ft (12.5m)	26ft (7.9m)	16ft (4.8m)	10ft (3.0m)
70W / 2.9A	226ft (68.8m)	142ft (43.2m)	89ft (27.1m)	56ft (17.0m)	35ft (10.6m)	22ft (6.7m)	14ft (4.2m)	8ft (2.4m)
80W / 3.3A	198ft (60.3m)	124ft (37.8m)	78ft (23.7m)	49ft (14.9m)	31ft (9.4m)	19ft (5.7m)	12ft (3.6m)	7ft (2.1m)
90W / 3.8A	176ft (53.6m)	111ft (33.8m)	69ft (21.0m)	43ft (13.1m)	27ft (8.2m)	17ft (5.1m)	10ft (3.0m)	6ft (1.8m)
100W / 4.2A	158ft (48.1m)	99ft (30.1m)	62ft (18.9m)	39ft (11.8m)	24ft (7.3m)	15ft (4.5m)	9ft (2.7m)	6ft (1.8m)
110W / 4.6A	144ft (43.8m)	90ft (27.4m)	57ft (17.3m)	35ft (10.6m)	22ft (6.7m)	14ft (4.2m)	9ft (2.7m)	5ft (1.5m)
120W / 5.0A	132ft (40.2m)	83ft (25.3m)	52ft (15.8m)	32ft (9.7m)	20ft (6.1m)	13ft (3.9m)	8ft (2.4m)	5ft (1.5m)
130W / 5.4A	122ft (37.1m)	76ft (23.1m)	48ft (14.6m)	30ft (9.1m)	19ft (5.7m)	12ft (3.6m)	7ft (2.1m)	4ft (1.2m)
140W / 5.8A	113ft (34.4m)	71ft (21.6m)	44ft (13.4m)	28ft (8.5m)	17ft (5.1m)	11ft (3.3m)	7ft (2.1m)	4ft (1.2m)
150W / 6.3A	105ft (32.0m)	66ft (20.1m)	41ft (12.5m)	26ft (7.9m)	16ft (4.8m)	10ft (3.0m)	6ft (1.8m)	4ft (1.2m)
160W / 6.7A	99ft (30.1m)	62ft (18.9m)	39ft (11.8m)	24ft (7.3m)	15ft (4.5m)	9ft (2.7m)	6ft (1.8m)	3ft (0.9m)
170W / 7.1A	93ft (28.3m)	58ft (17.6m)	36ft (10.9m)	23ft (7.0m)	14ft (4.2m)	9ft (2.7m)	5ft (1.5m)	3ft (0.9m)
180W / 7.5A	88ft (26.8m)	55ft (16.7m)	34ft (10.3m)	22ft (6.7m)	13ft (3.9m)	8ft (2.4m)	5ft (1.5m)	3ft (0.9m)
190W / 7.9A	83ft (25.3m)	52ft (15.8m)	33ft (10.0m)	20ft (6.0m)	13ft (3.9m)	8ft (2.4m)	5ft (1.5m)	3ft (0.9m)
200W / 8.3A	79ft (24.0m)	49ft (14.9m)	31ft (9.4m)	19ft (5.7m)	12ft (3.6m)	7ft (2.1m)	4ft (1.2m)	3ft (0.9m)
210W / 8.8A	75ft (22.8m)	47ft (14.3m)	29ft (8.8m)	18ft (5.4m)	11ft (3.3m)	7ft (2.1m)	4ft (1.2m)	2ft (0.6m)
220W / 9.2A	72ft (21.9m)	45ft (13.7m)	28ft (8.5m)	18ft (5.4m)	11ft (3.3m)	7ft (2.1m)	4ft (1.2m)	2ft (0.6m)
230W / 9.6A	69ft (21.0m)	43ft (13.1m)	27ft (8.2m)	17ft (5.1m)	10ft (3.0m)	6ft (1.8m)	4ft (1.2m)	2ft (0.6m)
240W / 10.0A	66ft (20.1m)	41ft (12.5m)	26ft (7.9m)	16ft (4.8m)	10ft (3.0m)	6ft (1.8m)	4ft (1.2m)	2ft (0.6m)
250W / 10.4A	63ft (19.2m)	40ft (12.1m)	25ft (7.6m)	15ft (4.5m)	9ft (2.7m)	6ft (1.8m)	3ft (0.9m)	2ft (0.6m)