

AERO TAPE SAUNA Indoor · Static White

Features

- Operates in temperature up to 212°F (100°C)
- Field cuttable
- Low voltage DC24V
- 100-300 lumen outputs
- IP65 rated, ideal for indoor uses
- 5 years warranty



Date _____ Fixture type _____

Project name _____ Project phase _____



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
AEROSN	W5 Wet (IP65)	24 DC24V	18 1800K	146 1.46W/ft -100 lm/ft
			22 2200K	293 2.93W/ft -300 lm/ft
			24 2400K	
			27 2700K	
			30 3000K	
			35 3500K	
			40 4000K	
			50 5000K	
			65 6500K	

Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length ¹		
F	Front	OW	Open wire 3.28'	F	Front	OW	Open wire 3.28'	Max.	16.4'	-1.46W
C	Closed	MC	Male connector with 0.98' cable	C	Closed	MC	Male connector with 0.98' cable	Increment	16.4'	-2.93W
		FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable			
		NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry			

1. Production length = Illuminated length + End cap extension length (refer to above "Dimension" section for extension length)

Temp./Color	1.46W/ft	2.93W/ft
1800K	151	299
2200K	156	310
2400K	162	321
2700K	171	339
3000K	178	353
3500K	178	353
4000K	184	364
5000K	182	361
6500K	180	357
Max. Run for Class 2 Low Voltage (ft)	16.4	16.4
Max. Run Length (ft)	16.4	16.4
Storage Temperature	-13-212°F	-13-212°F
Ambient Temperature	-4-212°F	-4-212°F

Technical Details

Width	0.47" (12mm)
PCB Width	0.39" (10mm)
LED Quantity	32 LEDs/ft (120 LEDs/M)
Beam Angle	120°
Efficacy	124.2lm/W @4000K 2.93W
CRI	Ra ≥ 80
LED MacAdam	3 steps
Life (L70)	> 54,000 hours
Max. Length Per Reel	16.4' (5M)

Feed Entry Options

F: Front

C: Closed



Connector Wire Options




OW: Open wire, Dry only
Standard 3.28' (1m), 20 AWG
(wire length customizable)

MC: Male connector, Wet. FC: Female connector, Wet.
Standard 0.98' (30cm), 20 AWG Standard 0.98' (30cm), 20 AWG


AERO TAPE SAUNA Indoor · Static White

Channel Compatibility


: No pixelation

Architectural


BE5075



BE3535




BE5035




Main lighting


BE6575



BE9358



BE60



AERO TAPE SAUNA Indoor · Static White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

Phase cut / Triac-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVF-24030-TDW	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.12" *0.78"
KVF-24060-TDW	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.00" *2.40" *0.94"
KVF-24096-TDW	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KVF-24150-TDW	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.00" *3.07" *1.85"
KVF-24200-TDW	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.00" *3.07" *1.85"
KVF-24300-TDW	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.85"

4 in 1-dimmable (0-10V/1-10V/Potentiometer/10V PWM)


Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVD-24030-DIM	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.12" *0.78"
KVD-24060-DIM	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.01" *2.40" *0.94"
KVD-24096-DIM	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KVD-24150-DIM	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVD-24200-DIM	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	13.38" *1.02" *7.28"
KVD-24300-DIM	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.89"

5 in 1-dimmable (Triac/0-10V/1-10V/Potentiometer/10V PWM)


Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVG-24030-DW	30W	100-277VAC	24V	Yes	Yes	Dry/Damp	6.10" *2.13" *0.79"
KVG-24060-DW	60W	100-277VAC	24V	Yes	Yes	Dry/Damp	7.01" *2.41" *0.94"
KVG-24096-DW	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.06" *2.76" *1.69"
KVG-24150-DW	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVG-24200-DW	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.08" *3.07" *1.85"
KVG-24300-DW	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.87" *3.07" *1.89"

Wiring Diagram

Non-dimmable



Dimmable



AERO TAPE SAUNA Indoor · Static White

Connectors (Optional, purchase for extra)

**CL-12-65**

Mounting clip, for 0.47" (12mm) tape, IP65

**SEC-C-12-65**

Closed silicone end cap, for 0.47" (12mm) tape, IP65

Additional Accessories (Optional, purchase for extra)

**MCW-2P-67**

Male connector with 0.98' (30cm) white cable, 2 pin, IP67, Wet, 20 AWG

**FCW-2P-67**

Female connector with 0.98' (30cm) white cable, 2 pin, IP67, Wet, 20 AWG

**VHB**

VHB 3M adhesive back tape, stronger stickiness