

LINIO NEON 360° RGB

Indoor · All-direction Bending · RGB

Features

- 360° emitting provides unparalleled creativeness
- Factory assembly
- Low voltage DC24V
- 50 lumen outputs
- IP65 rated, ideal for indoor uses
- 5 years warranty



Date


Fixture type

Project name

Project phase



Dimension

Standard
3.28' (1m)Ø
0.98" (25mm)

Order Code

Series	Environment	Voltage	Temp./Color	Power
LN360	W5 Wet (IP65)	24 DC24V	RGB RGB	305 3.05W/ft -50 lm/ft

Assembly Builder

End Cap ¹	Left Feed Entry	Right Feed Entry	Illuminated Length ²
IJ Injected (IP65)	F Front OW Open wire 3.28' S Side MC Male connector with 0.98' cable C Closed FC Female connector with 0.98' cable NA Only for Closed Feed Entry	F Front OW Open wire 3.28' S Side MC Male connector with 0.98' cable C Closed FC Female connector with 0.98' cable NA Only for Closed Feed Entry	Max. 16.4' -3.05W

1. Injected end cap is factory-made only.

2. Production length = Illuminated length + End cap extension length (refer to below page for extension length of each end cap)

Temp./Color	3.05W/ft
R	9
G	42
B	6
RGB	45
Max. Run for Class 2 Low Voltage (ft)	16.4
Max. Run Length (ft)	16.4
Storage Temperature	-13~140°F
Ambient Temperature	-13~113°F

Technical Details


Efficacy	13.7lm/W @RGB 3.05W
Beam Angle	360°
LED MacAdam	3 steps
Life (L70)	> 30,000 hours
Max. Length Per Reel	16.4' (5M)
Finish	Matte

LINIO NEON 360° RGB

Indoor · All-direction Bending · RGB

Feed Entry / End Cap Options

IJ: Injected end cap – IP65, factory-made only



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28' (1m), 20 AWG (wire length customizable)




MC: Male connector, **Wet**
Standard 0.98' (30cm), 20 AWG




FC: Female connector, **Wet**
Standard 0.98' (30cm), 20 AWG

Mounting Options



LN360-SFC-O

Name Surface mount clear bracket-open clip



LN360-SFC-C

Name Surface mount clear bracket-closed clip




LN360-SFC-L

Name Surface mount clear bracket-low profile clip




LN360-SFC-PC

Name Surface mount clear bracket-PC channel




LN360-SPC-O

Name Suspended mount clear bracket-open clip




LN360-SPC-C

Name Suspended mount clear bracket-closed clip



LN360-SPC-PC

Name Suspended mount clear bracket-PC channel




LN360-TLC-O

Name Telescoping clear bracket-open clip (Adjustable Length: 20-39")


LINIO NEON 360° RGB

Indoor · All-direction Bending · RGB




LIN360-TLC-C

Name Telescoping clear bracket-closed clip (Adjustable Length: 20-39")




LIN360-TLC-L

Name Telescoping clear bracket-low profile clip (Adjustable Length: 20-39")




LIN360-TLC-PC

Name Telescoping clear bracket-PC channel (Adjustable Length: 20-39")




LIN360-VB

Name Vertical metal flush surface mount bracket-black




LIN360-VSB

Name Vertical pendant suspended mount bracket-black




LIN360-UB

Name U-shaped metal flush mount bracket-black




LIN360-JNB-S

Name Metal joiner bracket-black (side cable entry only)




LIN360-JNB-C

Name Metal joiner bracket-black (closed end cap)



LIN360-JNC-S

Name Joiner bracket-clear (side cable entry only)



LIN360-JNC-C

Name Joiner bracket-clear (closed end cap)

LINIO NEON 360° RGB

Indoor · All-direction Bending · RGB

Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

DMX512-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KVX-24096-3C-A	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *3.07" *0.98"
KVX-24150-3C-A	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24200-3C-A	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24300-3C-A	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	11.85" *3.07" *0.98"

DMX Decoders


Code	Description
LT-903	3 channels output, up to 576W output power
LT-912	12 channels output, up to 1152W output power
LT-924	24 channels output, up to 1728W output power

Controllers


Code	Description
DINA-DR micro	DMX 60 channels, DMX Stand Alone controller with 10 scenes, USB connectivity for programming
SLESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes
STICK-GA2	DMX 512 channels, ready to use (pre-loaded with 8 scenes and 170 RGB fixtures)
STICK-CW4	DMX 1024 channels, up to 36 scenes stored and directly recalled via 6 touch sensitive buttons

Wiring Diagram

DMX Control System



DMX Driver System



Additional Accessories (Optional, purchase for extra)

			
MCW-4P-67 Male connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG	FCW-4P-67 Female connector with 0.98' (30cm) white cable, 4 pin, IP67, Wet, 20 AWG	MCB-4P-67 Male connector with 0.98' (30cm) black cable, 4 pin, IP67, Wet, 20 AWG	FCB-4P-67 Female connector with 0.98' (30cm) black cable, 4 pin, IP67, Wet, 20 AWG