

LINIO NEON 1615 TV RGB Outdoor · Vertical Bending · RGB

Features


- Max run length up to 42.6ft (13m) from single power feed
- Field cuttable & joinable
- Low voltage DC24V
- 100 lumen outputs
- IP67 rated, ideal for indoor and outdoor uses
- 5 years warranty



Date	Fixture type
Project name	Project phase



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
LN1615TV	W7 Wet (IP67)	24 DC24V	RGB RGB	335 3.35W/ft -100 lm/ft

Assembly Builder

End Cap ¹	Left Feed Entry	Right Feed Entry	Illuminated Length ²
IJ Injected (IP67)	F Front OW Open wire 3.28'	F Front OW Open wire 3.28'	Max. 42.6' -3.35W
IJC Clear injected (IP67)	B Bottom MC Male connector with 0.98' cable	B Bottom MC Male connector with 0.98' cable	Increment 4.92'
SEC Silicone (IP67)	S Side FC Female connector with 0.98' cable	S Side FC Female connector with 0.98' cable	
MEC1 Mechanical with screws (IP67)	C Closed NA Only for Closed Feed Entry	C Closed NA Only for Closed Feed Entry	
MEC3 Mechanical without screws (IP67)			

1. Injected and clear injected end cap are factory-made only.

2. Production length = Illuminated length + End cap extension length (refer to below page for extension length of each end cap)

Temp./Color	3.35W/ft
R	16
G	63
B	10
RGB	85
Max. Run for Class 2 Low Voltage (ft)	19.7
Max. Run for Mechanical end cap (ft)	21.3
Max. Run Length (ft)	42.6
Storage Temperature	-13-140°F
Ambient Temperature	-13-113°F


Technical Details

Efficacy	25.4lm/W @RGB 3.35W
Beam Angle	120°
Life (L70)	> 30,000 hours
Max. Length Per Reel	98.4' (30M)
Finish	Matte


LINIO NEON 1615 TV RGB Outdoor · Vertical Bending · RGB

Feed Entry / End Cap Options

IJ: Injected end cap – IP67, factory-made only



IJC: Clear injected end cap – IP67, factory-made only



SEC: Silicone end cap – IP67



MEC1: Mechanical end cap with screws – IP67



MEC3: Mechanical end cap without screws – IP67



LINIO NEON 1615 TV RGB Outdoor · Vertical Bending · RGB

Connector Wire Options

		
OW: Open wire, Dry only Standard 3.28' (1m), 20 AWG (wire length customizable)	MC: Male connector, Wet Standard 0.98' (30cm), 20 AWG	FC: Female connector, Wet Standard 0.98' (30cm), 20 AWG

Mounting Options

LN1615-SC

Name	Straight surface channel
Material	Aluminum
Standard Length	3.28' (1M)

LN1615-BC

Name	Bendable surface channel
Material	Aluminum
Standard Length	3.28' (1M)

LN1615-RC

Name	Straight recessed channel
Material	Aluminum
Standard Length	3.28' (1M)

LN1615-CL

Name	Mounting clip
Material	Stainless Steel
Standard Length	0.79' (20MM)

LINIO NEON 1615 TV RGB Outdoor · Vertical Bending · RGB

Drivers

Non-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"

DMX512-dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L*W*H)
KVX-24096-3C-A	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *3.07" *0.98"
KVX-24150-3C-A	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24200-3C-A	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24300-3C-A	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	11.85" *3.07" *0.98"

DMX Decoders


Code	Description
LT-903	3 channels output, up to 576W output power
LT-912	12 channels output, up to 1152W output power
LT-924	24 channels output, up to 1728W output power

Controllers


Code	Description
DINA-DR micro	DMX 60 channels, DMX Stand Alone controller with 10 scenes, USB connectivity for programming
SLESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes
STICK-GA2	DMX 512 channels, ready to use (pre-loaded with 8 scenes and 170 RGB fixtures)
STICK-CW4	DMX 1024 channels, up to 36 scenes stored and directly recalled via 6 touch sensitive buttons

Wiring Diagram

DMX Control System




DMX Driver System



LINIO NEON 1615 TV RGB Outdoor · Vertical Bending · RGB

Connectors (Optional, purchase for extra)



Additional Accessories (Optional, purchase for extra)

