

ANNO TAPE PRO TW Indoor · Tunable White

Features

- White COB with clean look, better color consistency
- Field cuttable & joinable
- Low voltage DC24V
- 240 lumen outputs
- IP20 rated, ideal for indoor uses
- 5 years warranty



Date	Fixture type
Project name	Project phase



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
ANNOP	D2 Dry (IP20)	24 DC24V	2765 2700K+6500K	305 3.05W/ft ~200 lm/ft

Assembly Builder

Left Feed Entry				Right Feed Entry				Illuminated Length ¹		
F Front	OW	Open wire 3.28'		F Front	OW	Open wire 3.28'		Max.	16.4'	~3.05W
C Closed	MC	Male connector with 0.98' cable		C Closed	MC	Male connector with 0.98' cable		Increment	1.97'	
	FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable				
	NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry				

Temp./Color	3.05W/ft
2700K	113
6500K	120
2700K+6500K	240
Max. Run for Class 2 Low Voltage (ft)	16.4
Max. Run Length (ft)	16.4
Storage Temperature	-13~140°F
Ambient Temperature	-4~113°F

Technical Details

Width	0.39" (10mm)
PCB Width	0.39" (10mm)
LED Quantity	195 LEDs/ft (640 LEDs/M)
Beam Angle	120°
Efficacy	78.7lm/W @2700K+6500K 3.05W
CRI	Ra≥90
Life (L70)	> 50,000 hours
Max. Length Per Reel	98.4' (30M)

Feed Entry Options



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28' (1m), 20 AWG
(wire length customizable)

MC: Male connector, **Wet**
Standard 0.98' (30cm), 20 AWG


FC: Female connector, **Wet**
Standard 0.98' (30cm), 20 AWG

ANNO TAPE PRO TW Indoor · Tunable White


Channel Compatibility

: No pixelation


Universal



Architectural




Main lighting




ANNO TAPE PRO TW Indoor · Tunable White

Special lighting

BE6728




BE2009




: Slight pixelation

Universal


BE2601



BE1204



BE1205



Drivers



Dimmable

Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
LM-100-24-U2A2	100W	100-277VAC	24V	Yes	No	Dry	13.86" *1.69" *1.18"

Wiring Diagram

TW Control Dimmable

0-10V Dimmable



ANNO TAPE PRO TW Indoor · Tunable White

Connectors (Optional, purchase for extra)



NCO-STCN-3P-10
Strip to cable connector without wire, for 0.39" (10mm) tape, 3 pin



NCO-STC-3P-10
Strip to cable connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 3 pin



NCO-STSJ-3P-10
Strip to strip jumper connector with 5.91" (15cm) wire, for 0.39" (10mm) tape, 3 pin



NCO-STMKB-3P-10

Strip to cable with black male & female connector, for 0.39" (10mm) tape, 3 pin



NCO-STMKW-3P-10

Strip to cable with white male & female connector, for 0.39" (10mm) tape, 3 pin



NI4CO-STs-3P-10
Strip to strip connector, for 0.39" (10mm) tape, 3 pin

Additional Accessories (Optional, purchase for extra)



MCW-3P-67
Male connector with 0.98" (30cm) white cable, 3 pin, IP67, Wet, 20 AWG



FCW-3P-67
Female connector with 0.98" (30cm) white cable, 3 pin, IP67, Wet, 20 AWG



VHB
VHB 3M adhesive back tape, stronger stickiness