

ANNO TAPE RGBWW Indoor · RGBWW

Features

- Max run length up to 16.4ft (5m) from single power feed
- Field cuttable
- Low voltage DC24V
- 270 lumen outputs
- IP20 rated, ideal for uses
- 5 years warranty




Date _____ Fixture type _____

Project name _____ Project phase _____



Dimension



Order Code

Series	Environment	Voltage	Temp./Color	Power
ANNO	D2 Dry (IP20)	24 DC24V	RGBWW2765 RGBWW (WW=2700K+6500K)	488 4.88W/ft ~270 lm/ft

Assembly Builder

Left Feed Entry				Right Feed Entry			Illuminated Length ¹		
F	Front	OW	Open wire 3.28'	F	Front	OW	Open wire 3.28'	Max.	16.4' ~4.88W
C	Closed	MC	Male connector with 0.98' cable	C	Closed	MC	Male connector with 0.98' cable	Increment	2.46'
		FC	Female connector with 0.98' cable			FC	Female connector with 0.98' cable		
		NA	Only for Closed Feed Entry			NA	Only for Closed Feed Entry		

Temp./Color	4.88W/ft
R	29
G	79
B	24
W27	67
W65	72
RGBWW2765	271
Max. Run for Class 2 Low Voltage (ft)	15.7
Max. Run Length (ft)	16.4
Storage Temperature	-13-140°F
Ambient Temperature	-4-113°F

Technical Details

Width	0.47" (12mm)
PCB Width	0.47" (12mm)
LED Quantity	170 LEDs/ft (560 LEDs/M)
Beam Angle	180°
Efficacy	55.5lm/w @RGBWW2765 4.88W
CRI	Ra≥90
Life (L70)	> 30,000 hours
Max. Length Per Reel	98.4' (30M)

Feed Entry Options



Connector Wire Options



OW: Open wire, **Dry only**
Standard 3.28' (1m), 20 AWG
(wire length customizable)

MC: Male connector, **Wet**
Standard 0.98' (30cm), 20 AWG

FC: Female connector, **Wet**
Standard 0.98' (30cm), 20 AWG


ANNO TAPE RGBWW Indoor · RGBWW

Channel Compatibility


: No pixelation

Universal


BEI415




BE2015




BEI202




BEI201




BEI207




BEI910




BE2810




BEI203




BE2020



BEI206




BE60




Architectural


BE5615




BE7615




BE5315




BE5035




BE3535




BE5075




BE4615



BEI3350



BEI402




BEI403




Main lighting

BE6575



BE9358




ANNO TAPE RGBWW Indoor · RGBWW

Special lighting

BE6728




BE6826



BEI2017




BE6916



BE3511




BE9151




: Slight pixelation

Universal


BE2601



BE1204



BE1205



ANNO TAPE RGBWW Indoor · RGBWW

Drivers

Non-dimmable							
Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KV-24030-ASW	30W	100-277VAC	24V	No	Yes	Dry/Damp	6.10" *2.12" *0.78"
KV-24060-ASW	60W	100-277VAC	24V	No	Yes	Dry/Damp	7.00" *2.40" *0.94"
KV-24096-ASW	96W	100-277VAC	24V	No	Yes	Dry/Damp/Wet	9.05" *2.75" *1.69"
KV-24150-ASW	150W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24200-ASW	200W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.07" *3.07" *1.85"
KV-24300-ASW	300W	100-277VAC	24V	No	No	Dry/Damp/Wet	10.86" *3.07" *1.85"


DMX512-dimmable							
Code	Max Load	Input	Output	Dimmable	Class 2	Environment	Size (L *W *H)
KVX-24096-5C-A	96W	100-277VAC	24V	Yes	Yes	Dry/Damp/Wet	9.05" *3.07" *0.98"
KVX-24150-5C-A	150W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24200-5C-A	200W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	10.90" *3.07" *0.98"
KVX-24300-5C-A	300W	100-277VAC	24V	Yes	No	Dry/Damp/Wet	11.85" *3.07" *0.98"

Code	Description
LT-905	5 channels output, up to 600W output power


Code	Description
DINA-DR micro	DMX 60 channels, DMX Stand Alone controller with 10 scenes, USB connectivity for programming
SIESA-U9	DMX 256 channels, USB connection, standalone mode with 1 area and 20 scenes
STICK-GA2	DMX 512 channels, ready to use (pre-loaded with 8 scenes and 170 RGB fixtures)
STICK-CW4	DMX 1024 channels, up to 36 scenes stored and directly recalled via 6 touch sensitive buttons

Wiring Diagram

DMX Control System



DMX Driver System



Additional Accessories (Optional, purchase for extra)



VHB
VHB 3M adhesive back tape, stronger stickiness